
Optimized Tool Distribution Exclusive Helix Distribution



Optimized design with exclusive special helix distribution, with only one hammer touching the material at a time.

Rotor Bearings with Forged Steel Reinforced Bearing Housing



Reinforced and oversized bearing housings for the rotor made from forged steel. Maximum protection for the oversized bearings with double row of spherical rollers.



SEVERE DUTY

Rotor Housing

Rotor Bearings

Replaceable and Interchangeable Rotor Cutting Tools

HEAVY DUTY / EXTREME DUTY











Side Scrapper

For use with standard, vegetation, wood, and grass. Not for use with stones.

HEAVY DUTY			EXTREME DUTY		SEVERE DUTY	
190510	190515	190520	190555	190565	190605	190615
4-10 Tons			10-16 Tons		16-20 Tons	
8,800 - 22,000			22,000 - 35,000		35,000 - 44,000	
30"	40"	50"	40"	50"	40"	50"
40"	52"	60"	54"	64"	54"	64"
2,600 - 4,000 PSI			4,000 - 5,500 PSI		4,000 - 5,500 PSI	
10 – 24 GPM	14 – 35 GPM	16 – 35 GPM	26 – 40 GPM		38 – 50 GPM	40-50 GPM
13"			15"		16"	
18 + 2 (F09)	24 + 2 (F09)	30 + 2 (F09)	24 + 2 (F09)	30 + 2 (F09)	22 (F19) + 2 (F20)	28 (F19) + 2 (F20)
4 groove belts (XPB)			1 synchronous belt (Polychain GT Carbon)		1 synchronous belt (Polychain GT Carbon)	
893 lbs	1,015 lbs	1,147 lbs	1,665 lbs	1,830 lbs	2,402 lbs	2,822 lbs
Manually Adjustable (26 - 45 cc Bosch Rexroth)		Variable Displacement (55 - 85cc Bosch Rexroth)		Variable Displacement (80 - 115cc Bosch Rexroth		
2,185 - 2,840 rpm	2,115 - 2,890 rpm	2,310 – 2,890 rpm	1,820 - 2,730 rpm		2,190 - 2,815 rpm	
3			5		4	
Replaceable - Non Adjustable			Replaceable - Adjustable /2 Positions		Replaceable - Adjustable /3 Positions	
Replaceable Bolted Liner			Replaceable Bolted Liner		Replaceable Bolted Liner	
1 - Double Curtain			1 - Double Curtain		2 - Double Curtain	
Mechanical Adjustable Door			Hydraulic Door w Counterblade		Hydraulic Door w Counterblade	
4 Inch			7 Inch		8 Inch	
	30" 40" 10 – 24 GPM 18 + 2 (F09) 893 lbs Manually Adju 2,185 - 2,840 rpm Repla	190510 190515 4-10 Tons 8,800 - 22,000 30" 40" 40" 52" 2,600 - 4,000 PSI 10 - 24 GPM 14 - 35 GPM 13" 18 + 2 (F09) 24 + 2 (F09) 4 groove belts (XPB) 893 lbs 1,015 lbs Manually Adjustable (26 - 45 cc B 2,185 - 2,840 rpm 2,115 - 2,890 rpm 3 Replaceable - Non Adjus Replaceable Bolted Lint 1 - Double Curtain Mechanical Adjustable	190510 190515 190520	190510 190515 190520 190555 4-10 Tons 10-1 8,800 - 22,000 22,000 30" 40" 50" 40" 40" 52" 60" 54" 2,600 - 4,000 PSI 4,000 - 4,000 PSI 4,000 - 26 - 4,000 PSI 26 - 45 GPM 10 - 24 GPM 14 - 35 GPM 16 - 35 GPM 26 - 45 GPM 13" 24 + 2 (F09) 30 + 2 (F09) 24 + 2 (F09) 4 groove belts (XPB) 1 synchronous belt 1,900 Feb GPM 1,665 lbs Manually Adjustable (26 - 45 cc Bosch Rexroth) Variable Displacement 2,185 - 2,840 rpm 2,115 - 2,890 rpm 2,310 - 2,890 rpm 1,820 - 3 3 Replaceable - Non Adjustable Replaceable - Ad Replaceable Bolted Liner Replaceable - Ad 1 - Double Curtain 1 - Double Curtain 1 - Double Curtain 1 - Double Curtain 1 - Double Curtain 1 - Double Curtain	190510 190515 190565 4-10 Tons 10-16 Tons \$10-16 Tons \$2,000 - 22,000 35,000 30" 40" 50" 40" 50" 40" 52" 60" 54" 64" 10 - 24 GPM 14 - 35 GPM 15" 18 + 2 (F09) 24 + 2 (F09) 30 + 2 (F09) 4 groove belts (XPB) 1 synchronous belt (Polychain GT Carbon) 893 lbs 1,015 lbs 1,147 lbs 1,665 lbs 1,830 lbs Manually Adjustable (26 - 45 cc Bosch Rexroth) Variable Displacement (55 - 85cc Bosch Rexroth) 2,185 - 2,840 rpm 2,310 - 2,890 rpm 1,820 - 2,730 rpm 3 5 Replaceable - Non Adjustable Replaceable - Adjustable /2 Positions Replaceable Bolted Liner 1 - Double Curtain Hydrau	190510 190515 190565 190565 190605 4-10 Tons 10-26 8,800 - 22,000 35,000 35,000 30" 40" 50" 40" 50" 40" 50" 40" 54" 64" 54" 10 - 24 GPM 14 - 35 GPM 16 - 35 GPM 26 - 40 GPM 38 - 50 GPM 18 + 2 (F09) 24 + 2 (F09) 30 + 2 (F09) 22 (F19) + 2 (F20) 18 + 2 (F09) 24 + 2 (F09) 30 + 2 (F09) 22 (F19) + 2 (F20) 1 + 2 (F09) 30 + 2 (F09) 22 (F19) + 2 (F20) 4 groove belts (XPB) 1 synchronous belt (Polychain GT Carbon) 1 synchronous belt (Polychain GT Carbon)



ABOUT BLUE DIAMOND® ATTACHMENTS

Blue Diamond® Attachments is a trusted and reliable company. Established in 1995, Blue Diamond® is a widely recognized name in the global attachments industry. We are committed to unparalleled customer service from the very first call to the after-sale followup and service.

In today's fast-paced environment, delivering quickly and on time are key to success. Blue Diamond® Attachments is very different in the fact that we stock thousands of finished products in our warehouses every day ready to ship. This results in a big advantage for our customers with many shipments leaving in 2–3 days. Our Tennessee facilities alone are now over 250,000-square-feet situated on 32 acres. These facilities, along with streamlined processes, allow most of our orders to leave our facility within 10 days.

Our parts department keeps thousands of replacement parts at the ready and strives to ship all parts orders received before noon the same day the order is placed! Tracking numbers are sent to our customer the day after the shipment leaves our dock.

We are located in Knoxville, Tennessee. This central location allows our products to reach more than half of the United States population within 2–3 days' shipping time. We have many loading docks, which allow us to keep trailers from several freight companies, making use of the best freight lines available. In addition, we are the only 1-day point of export to multiple foreign



4512 Anderson Road | Knoxville, TN 37918 ph 888-376-7027 | fax 865-246-2007









©2024 Blue Diamond® Attachments. All Rights Reserved.

YOUR AUTHORIZED BLUE DIAMOND DEALER IS:

3/28/24









DRUM MULCHER ATTACHMENT GUIDE







Mechanical Adjustable Door 2 Position – Open and Closed



Wear Resistant Steel Skids Bolted for Easy Replacement



Hydraulic Piston Motor Manually Adjustable Displacement Motor (45cc)



Hydraulic Adjustable Door Replaceable Counterblade Bolted to Door



Hydraulic Piston Motor Variable Displacement Motor (85cc)



Hydraulic Adjustable Door Replaceable Counterblade Bolted to Door



Hydraulic Piston Motor Variable Displacement Motor (115cc)

Wear Resistant Steel Skids 3 Adjustable Positions Bolted for Easy Replacement

• 4T-10T



MACHINE SIZE

4T-10T



GPM 10-35 GPM



MOTOR SIZE 26-45cc



CUTTING DIAMETER





WEIGHT 893/1,015/1,147 lbs



2 Adjustable Positions

Bolted for Easy Replacement



MACHINE SIZE 10T-16T



26-40 GPM



55-85cc

MOTOR SIZE



CUTTING DIAMETER



WEIGHT 1,665/1,830 lbs



MACHINE SIZE

16T-20T



38-50 GPM



80-115cc

CUTTING DIAMETER




2,402/2,822 lbs



Centralized Hydraulic Ports and Greasing Points Easy Hookup and Maintenance



Steel Counterblades Reversible and Bolted for Easy Replacement




Chain Protection Curtains Protects Operator from Flying Debris



Drive System 4 XPB drive belts



Input Counterblade Adjustable & Bolted for Easy Replacement




and Greasing Points Easy Hookup and Maintenance

Centralized Hydraulic Ports



Reversible and Bolted for Easy Replacement



Single Double Chain Curtain Protects Operator from Flying Debris



Synchronous Drive System Oversized Poly Chain® drive belt



Input Counterblade Adjustable & Bolted for Easy Replacement



450 Grade Steel Counterblades Replaceable and Bolted for Easy Replacement



2 Double Chain Curtains Extra Protection from Flying Debris



Synchronous Drive System Oversized Poly Chain® drive belt



Input Counterblade Adjustable & Bolted for Easy Replacement